

## Powder extinguishers

Powder is a very good extinguishing agent, which can be used for almost every fire class.

The extinguishing effect of powder is especially based on the anti-catalytic effect. Use of powder can result in considerable damage. However, powder has great advantages, such as its resistance to frost and the fact that it doesn't conduct electricity.

### Powder extinguisher GD2G

Contains ABC-powder under permanent pressure.  
This extinguisher will be delivered with marine bracket.

| Type                       | GD2G       |
|----------------------------|------------|
| Contents (kg)              | 2          |
| Performance                | 13A 89B C  |
| Total weight (kg)          | 3,4        |
| Height (mm)                | 315        |
| Largest width (mm)         | 145        |
| Working pressure (bar)     | 15         |
| Operating temperature (°C) | -30 to +60 |
| Part number                | 809-193002 |



GD2G

### Powder extinguisher PEP 6 GA and PEP 12 GA

Contains ABC-powder and a CO2 cartridge.




| Type                       | PEP 6 GA   | PEP 12 GA  |
|----------------------------|------------|------------|
| Contents (kg)              | 6          | 12         |
| Performance                | 27A 144B C | 43A 233B C |
| Total weight (kg)          | 10,1       | 19         |
| Height (mm)                | 540        | 640        |
| Largest width (mm)         | 270        | 320        |
| CO2 cartridge (gr)         | 140        | 280        |
| Operating temperature (°C) | -20 to +60 | -20 to +60 |
| Part number                | 809-307710 | 809-307730 |



PEP 6GA / PEP 12 GA

## Powder extinguisher GP6-c, GP9-c and GP12-c



Contains ABC-powder and a CO2 cartridge.

| Type                       | GP6-c  | GP9-c  | GP12-c  |
|----------------------------|---|---|--|
| Contents (kg)              | 6   | 9   | 12   |
| Performance                | 43A 233B C  | 43A 233B C  | 55A 233B C   |
| Total weight (kg)          | 10,5  | 15,2  | 19,5   |
| Height (mm)                | 495   | 560   | 595  |
| Largest width (mm)         | 270   | 280   | 290  |
| CO2 cartridge (gr)         | 140   | 210   | 280  |
| Operating temperature (°C) | -30 to +60  | -30 to +60  | -30 to +60   |
| Part number                | 809-193106  | 809-193109  | 809-193112   |



## Powder extinguisher GP6, GP9 and GP12

Contains ABC-powder under permanent pressure.


| Type                       | GP6  | GP9  | GP12  |
|----------------------------|---|---|--|
| Contents (kg)              | 6   | 9   | 12   |
| Performance                | 34A 233B C  | 43A 233B C  | 55A 233B C   |
| Total weight (kg)          | 9,2   | 13,5  | 17,4   |
| Height (mm)                | 510   | 605   | 600  |
| Largest width (mm)         | 215   | 226   | 239  |
| Working pressure (bar)     | 15  | 15  | 15   |
| Operating temperature (°C) | -30 to +60  | -30 to +60  | -30 to +60   |
| Part number                | 809-193006  | 809-193009  | 809-193012   |



## Wheeled powder extinguisher GA50 / GA50N

Suitable for extinguishing class A, B, and C fires to EN2.

With external propellant-cylinder filled with Nitrogen and a flexible rubber high-pressure hose with extinguishing powder pistol.

| Type                       | GA50  | GA50N      |
|----------------------------|--|------------|
| Contents (kg)              | 50   | 50         |
| Extinguishing agent        | Amron 40, ABC  | MAP30, ABC |
| Total weight (kg)          | 98   | 84         |
| Height (mm)                | 1110   | 1050       |
| Largest width (mm)         | 450  | 440        |
| Hose length (m)            | 10   | 10         |
| Propellant (l, bar)        | 3, 150   | 3, 140     |
| Operating temperature (°C) | -30 to +60   | -30 to +60 |
| Part number                | 809-190120   | 809-190128 |



Fire extinguishing systems

Fire detection

**Hose reels and extinguishers**

Emergency lighting

Training and consultancy

Service and maintenance

Burglary protection

Access Control

Camera Security

Terrain Protection

Alarm monitoring Services

Remote servicing

**Ajax Chubb Varel**

Marine & Offshore Department

T: +31 (0)180 - 555 222

E: [marine@ajaxchubbvarel.nl](mailto:marine@ajaxchubbvarel.nl)

I : [www.ajaxchubbvarel.nl](http://www.ajaxchubbvarel.nl)